



PCT/EP 03 / 093 49<sup>#2</sup>  
Rec'd PCT/ 23 FEB 2005

INVESTOR IN PEOPLE

EP 03 / 09349

REC'D 26 NOV 2003

WIPO PCT

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

*Stephen Handley*

Dated

7 October 2003

BEST AVAILABLE COPY

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

Patents Act 1977  
(Rule 16)

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



1/77

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference	JWB/SS/58179		
2. Patent application number (The Patent Office will fill in this part)	0219745.7		24AUG02 E743503-3 C03008 P01/7700 0.00-0219745.7
3. Full name, address and postcode of the or of each applicant (underline all surnames)	FAST Technology AG, Otto-Hahn-Str. 24, Gewerbegebiet Riemerling, D-85521 Ottobrunn, Germany. Patents ADP number (if you know it) 8174880001 If the applicant is a corporate body, give the country/state of its incorporation Germany		
4. Title of the invention	Torque Sensor Adaptor		
5. Name of your agent (if you have one)	Lloyd Wise, Tregear & Co.		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Lloyd Wise, Tregear & Co., Commonwealth House, 1-19 New Oxford Street, London WC1A 1LW. Patents ADP number (if you know it) 117001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications (and if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application		Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	Yes		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 13 /

Claim(s) 5 /

Abstract

Drawing(s) 2 + 2 R

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1 /

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature *Lloyd Wise, Tregear & Co.* Date 23 August 2002

Lloyd Wise, Tregear & Co.

12. Name and daytime telephone number of person to contact in the United Kingdom John William BLUFF (020) 7571 6200

Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay, please contact the Patent Office.*

Title: Torque Sensor Adaptor

FIELD OF THE INVENTION

This invention relates to a torque transducer assembly and to a torque transducer incorporating such an assembly. The invention has particular  
5 application to measuring torque in a fastening tool in which torque is generated in pulses and to measuring torque in an adaptor mountable to a pulsed-torque type of fastening tool.

The invention further relates to an electrical power generator for generating power from mechanical vibrations such as are generated in pulse-  
10 type fastening tools.

BACKGROUND TO THE INVENTION

Considerable attention has been given in recent times to measuring the torque-generated in pulsed torque tools and controlling operation of the tool to achieve a pre-determined torque. Such tools may be sometimes referred to  
15 as powered torque wrenches. They have been long used for applying a tightening torque to fasten nuts to bolts, or similar operations.

Pulsed torque tools include two categories. One in which an impact generates a torque impulse, such as rotary hammer and anvil mechanisms: the other in which a pulse of controlled characteristics is generated, such as  
20 by a pressure pulse generated with the aid of a piston and cylinder mechanism. In both cases, a train of successive torque pulses is generated to produce increasing torque on the load being tightened. Impact-type tools may be electrically or pneumatically driven (e.g. compressed air). Pressure pulse-type tools may be hydraulically driven (e.g. oil) or electrically driven.  
25 The torque pulses are generated at one end of an output shaft and are transmitted to an adaptor at the other end configured to fit the load such as a nut or bolt head.

The control of a power impact tool using a torque transducer is described in published U.S. patent application US2002/0020538A1. The torque transducer uses a ferromagnetic sensor and specifically discloses a magneto-elastic ring coupled to the output shaft of the tool. An impact tool control method and apparatus is described in International patent application publication WO01/44776. The control system uses a magneto-elastic torque transducer mounted exteriorly of the tool in which the magneto-elastic transducer element is an integral portion of a shaft through which torque is transmitted. This document also discloses the implementation of the control system as a retrofit system for use in controlling an existing impact tool.

PCT patent application PCT/EP02/06960 filed 24<sup>th</sup> June, 2002 discloses the control of a pulsed torque tool using magnetic-based torque transducer which has a transducer element or region integral with the output shaft of the tool. The control apparatus including the transducer disclosed in this application is disposed interiorly of the power torque tool.

The present invention arises from addressing the problem of providing an adaptor attachable to a conventional power torque tool of the pulsed-type whereby torque measurement and control can be exercised on the tool. The invention is also concerned with measuring the torque generated on a load by each pulse in order to exercise control of the application of torque to the load and particularly to stop operation of the power tool when a predetermined torque is reached. Another aspect of the invention also proposes using the mechanical vibration associated with the operation of a power torque tool to derive electrical energy for operating circuitry for the measurement and control procedures. This aspect of the invention is of more general utility for generating electrical energy from mechanical vibration.

Aspects and features of this invention relating to a torque transducer assembly suitable for use in an adaptor are set forth in Claims 1 to 7 and 22

following this description. The invention also provides a torque transducer as set forth in Claim 8 to <sup>1</sup>~~10~~.

Aspects and features of this invention relating to an electrical power generator in accordance with this invention are set forth in Claims <sup>2</sup>~~11~~ to 20.

5 The generator may be mounted to a pulsed-type power torque tool.

The invention and its practice will be further described with reference to the accompanying drawings:

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a diagrammatic view of a torque sensor adaptor kit for a  
10 conventional power torque tool in accordance with this invention;

Fig. 2 shows an axial cross-sectional view through an adaptor for use as the torque sensor adaptor shown in Fig. 1;

Fig. 3 shows an axial cross-sectional view through another torque sensor adaptor showing additional mechanical detail;

15 Fig. 4 illustrates a signal-processing feature employed in the measurement/control unit of Fig. 1;

Fig. 5 shows an axial view through one embodiment of a vibration-powered electrical generator unit according to the invention; and

20 Fig. 5a shows the coil of the unit connected with a rectifier for generating a direct voltage output.

#### DESCRIPTION OF EMBODIMENT OF ADAPTOR KIT

Fig. 1 shows a conventional power torque tool 10, such as an impact-type fastening tool which provides torque pulses at an output shaft 12. The tool illustrated is powered by compressed air through line 14. It is

conventional to fit a load-engaging adaptor on the end 12a of the shaft 12 distal the power tool for transmitting torque to the load, e.g. a nut or bolt head. Such an adaptor is exemplified in PCT/EP02/06960. The adaptor is a passive article for transmitting torque from the shaft to the load. As described in  
5 PCT/EP02/06960, the disclosure of which is hereby incorporated by reference, torque measurement and control is performed within the tool body 10.

In accordance with one aspect of the present invention a kit including a torque sensor adaptor 20 is provided to enable torque measurement and  
10 control to be exercised on a conventional pulsed torque tool not containing such provision. The adaptor 20 couples to the tool output shaft at one end and receives a conventional passive adaptor for engaging a load at the other end. The adaptor incorporates a torque transducer arrangement using a magnetic-based torque transducer element. The adaptor 20 can be  
15 characterised as an active device in contrast to prior passive devices. In the kit illustrated the torque-dependent signals from the sensor arrangement in adaptor 20 are supplied over cable connection 22 to a signal processing and controller unit 30 which in turn supplies a shut-off signal over cable connection 32 to an air-valve unit 40 acting in line 14. The unit 30 may include a display  
20 34, e.g. an LCD display, for displaying relevant parameters on a manually actuable key pad 36 for entering control instructions and data to a programmed microprocessor (not shown) housed in unit 30. The unit 30 can be mounted or carried so as to be free of the vibration generated in operation of the tool 10. As schematically illustrated by chain lines 24 the adaptor 20  
25 has a body portion 26 which is securable or attachable to the body of the power tool 10 as will be described below. The adaptor has a torque transmitting shaft extending through the body and having an output end 28.

Fig. 2 shows one form of construction for the adaptor 20 which is constructed to transmit torque about an axis A-A. It is a general aim of the

construction to keep the axial length of the torque transmitting shaft as short as possible. The adaptor has a housing 26 with an internal circular bore 27 in which is mounted a torque transmitting transducer assembly 60 rotatable within the housing 26 about central axis A-A. Details of support and mounting are shown in Fig. 3

The assembly 60 has a shaft portion 62 disposed between an input portion 64 and an output portion 66 providing the output end 28 of Fig. 1. The input and output roles are reversible but the shaft portions 62 and 64 are shaped in accord with usual power tool practice. The input portion 64 is engaged with to the shaft 12 of tool 10. It is of larger diameter than the shaft portion 62 and includes an axial blind bore 68 configured to fit on the distal end 12a of the tool output shaft 12. For example, if the tool output shaft is of a square cross-section, the bore 68 is of a matching square section. The output portion 66 is shown in this embodiment as a square cross-section shaft similar to the output shaft 12 of the power tool and to which a passive load-engaging adaptor can be fitted. It will be understood that the input and output portions of the assembly 60 can be configured as required by the tool and the load adaptor respectively; or the output portion 66 could be configured for direct engagement with the load.

The shaft portion 62 is of circular cross-section and is radially-spaced from the adjacent inner surface of housing 26. Shaft portion 62 is magnetised at 70 to provide a torque-sensitive transducer element or region which emanates a torque-dependent magnetic field which is sensed by a sensor arrangement 72.

The region 70 is a region of stored magnetisation. That is, it is remanently magnetised to store a permanent magnetisation. Preferably the magnetisation is an annulus of longitudinal magnetisation about axis A-A. Longitudinal magnetisation is in the direction of axis A-A. The longitudinal



magnetisation may be of the kind known as circumferential sensing as disclosed in WO01/13081 or, preferably, of the kind known as profile-shift (axial or radial sensing) as disclosed in WO01/79801. Another torque measuring technique which does not require a region of stored magnetisation is that disclosed in British patent application GB 0204213.3 filed 22<sup>nd</sup> February, 2002. In this technique the transducer element is not a previously magnetised or (encoded) region of the shaft but is a defined region in which the torque-sensitive element is established in use.

The magnetic field sensor arrangement is disposed in the space between the portion 62 and the adjacent interior surface 27 of housing 26. As will become more apparent from the adaptor of Fig. 3, the space preferably houses a ring of material in which the sensor arrangement is embedded and a portion of which provides a bearing supporting shaft portion 62. Various magnetic field sensor devices are known in the art, e.g. Hall effect and magnetoresistive, but a preferred sensor device is a saturating-core inductor device, particularly a saturating-core device or devices connected in a signal conditioning and processing circuit (SCSP) of the kind described in WO98/52063. The complete sensor circuit arrangement is mounted to housing 26 within bore 27. The signal output cable 22 (Fig. 1) exists through the aperture 11. The sensor device(s) and the associated SCSP are not in contact with the shaft.

By way of example, Fig. 2 illustrates the SCSP 72 as including two saturating core sensor devices (MFS) 74a, 74b. As is described in WO01/13081 and WO01/79801, two devices connected in series in an SCSP circuit can be employed to additively combine torque-dependent components of the field emanated by region 70 while cancelling out a common component such as the Earth's magnetic field or an interfering component associated with power tool at the workpiece to which torque is applied. The placement and

orientation of the sensor inductors is dependent on the torque-dependent component to be sensed.

The signal outputted on cable 22 is a train of pulses corresponding to the successive impacts in the power tool or other apparatus generating pulses of torque. Each pulse of the output train has an amplitude and duration representing the torque attained and the time over which the torque acts to turn or attempt to turn the load. The train of torque-representing pulses are processed by the programmed microprocessor in unit 30 to determine at which point a pre-set torque is reached. The pre-set value is input by keypad 36. Proposals for determination of the torque achieved are discussed in U.S. 2002/002050538 A1 and WO01/44776. More detailed information on the generation of torque over a successive number of pulses and its measurement is disclosed in PCT/EP02/06960.

On attaining a desired measured torque the microprocessor in unit 30 outputs a signal on cable 32 to actuate an air-valve controller 40 to shut-off the air or other power supply to the power torque tool 10.

In an alternative arrangement the SCSP circuit is included in unit 30 so that only the MFS devices are included within the adaptor and connected into the SCSP through the cable 22.

In implementing torque measurement using the adaptor described it has been found beneficial to make a measurement for each torque pulse signal which is referenced to the quiescent level of the signal output from SCSP 72. This enables drift in the output of the SCSP to be disregarded. Fig. 4 shows the output voltage  $V_T$  of the SCSP over a number of pulses at which the quiescent level  $V_0$  drifts (the drift is exaggerated). The pulse amplitude  $V_P$  should be measured with respect to the quiescent level. Pulse detection and measurement is preferably done using a sampling technique enabling up to, say, 20 samples to be taken during the period of a pulse.

Investigation to date has revealed that the external active adaptor now proposed is likely to be more subject to interfering magnetic fields originating outside the power tool than a power tool in which magnetic-based torque measurement is made internally. On the other hand, measurement drifts and variations due to part tolerances are likely to be better in the external adaptor than with a magnetic-based torque transducer within the power tool.

It is recognised that the active torque sensor device may have a limited life expectancy. It is used in a hostile environment. In addition to the inherently vibratory nature of a power pulse torque tool, additional mechanical stresses arise in the way the tool is applied to fasten a wheel nut. The angle of the tool to the next axis varies, the stiffness of the nut on the engaged thread is another variable and the power tool may run at a very high speed if operated under no-load conditions. One additional feature that can be provided in the unit 30 is to count the number of torque pulses detected and processed as a measure of the use of the adaptor. An indicator can be displayed on the display screen 34 when a predetermined number of pulses have been recorded.

Turning now to Fig. 3, the torque sensor adaptor 120 performs and operates in the same manner as that of Fig. 2 and those details of the sensor assembly will not be repeated. Fig. 3 shows additional details of one embodiment of the mechanical structure of the active adaptor. Features like or similar to those of Fig. 2 bear the same reference numerals increased by 100.

In Fig. 3, the rotatable transducer shaft assembly 160 comprises an input portion 164, a transducer region 162 (the stored magnetisation is not illustrated), and an output portion 126. The assembly is rotatably mounted in housing 126. The output portion of square cross section includes recess 165 for co-operating with a standard passive adaptor. The transducer region 162

is located for rotation within the housing by a plain bearing provided by an annular bush 180 of a plastics material which is bonded to or otherwise secured against rotation to a forward (i.e. toward the output end) inside surface 127a of the housing 126. The interior diameter of bush 180 is slightly  
5 greater than the diameter of region 162, other than for a forward lip 182 which bears against the shaft. The bush 180 has the sensor devices 174a, 174b embedded within it. In the construction of Fig. 3 it is assumed that the SCSP circuit is external to the adaptor in the unit 30 of Fig. 1. The cable exit hole is not shown.

10 The rearward end of bush 180 seats against an internal step 127b of housing 126 and also provides an abutment 184 for axially locating the transducer assembly and specifically a forward surface of the enlarged input portion 164. The input portion is sized to rotate freely within a part 126a of the housing of reduced internal diameter extending from step 127b to a rearward  
15 internal step 127c. Step 127c lies adjacent a circumferential groove 165 in the input portion 164. An annular bushing 186 of a low friction, self-lubricating material is received in the groove and engages the interior surface of housing 126 and is axially located by step 127c. The bushing 186, and therewith the transducer assembly 160 is retained in the housing by an internally-located  
20 press-fit retaining ring 188 at the rear of the housing. The housing 126 not only provides mechanical support and protection but provides a magnetic shield for the transducer assembly. It will be understood that the construction illustrated in Fig. 3 is diagrammatic in nature.

One feature of the assembly 160 of Fig. 3 which differs from that of  
25 assembly 60 of Fig. 2 is that the input portion 164 terminates at 164a flush with the rearward end 126b of the housing 126 or within the axial confines of the housing which is in accord with the desire to keep the overall length of the active adaptor as small as possible. The square-section bore 168 for

engaging the output shaft of the power tool is contained within the housing. The assembly 160 is a push fit into the housing 126 from its rearward end.

To perform the function generally indicated at 24 in Fig. 1 of preventing rotation of the adaptor housing and to retain the output shaft of the power tool engaged within the bore 168, the exterior of housing 126 is adapted to retain one end of a stiff helical spring (or more than one such spring) the other end of which is retained on the housing of the power tool. The spring, thus retained, is in an axially stretched state (in tension) so that the tension maintains the active adaptor engaged with the power tool. It has also been found that the flexibility of the retaining spring enables the power tool fitted with the active adaptor to accommodate the variations in the angle between the torque axis and the load being fastened that occur in practical use of the tool. It will be understood the plain bearing type of rotary support provided by bush 180 and bushing 186 could be substituted by other means of bearing support.

If a cable 22 is used the cable can be secured to the power tool body. The unit 30 can be mounted anywhere convenient, e.g. on the airline 14 or the valve unit 40. There is advantage in using a wire-less link (free of wire connection) from the active adaptor.

The operation of the kit described requires electrical power to be available to operate the SCSP in the adaptor 20 and the electronics in unit 30. While such power can be derived from any source, it is preferred to make the kit fittable to any power torque tool without any special electrical power connection requiring to be made other than for the air valve control unit 40 which becomes part of the energy supply (air or otherwise) for the tool.

To this end the unit 30 may be battery powered and power to the SCSP in adaptor 20 supplied through the cable 22. To at least support the internal battery supply, it is now proposed to provide a means for electrical

power generation which draws its energy from the mechanical vibration of the power torque tool. Such a source would be of particular benefit where the active adaptor 20, 120 does not use any form of cable communication to unit 30. Both from the point of view of compactness and of reliability of operation  
5 in an environment of high vibration, avoidance of a battery supply at the adaptor is desirable.

### DESCRIPTION OF ELECTRICAL POWER GENERATOR

A vibration-to-electrical power generator will now be described with reference to Figs. 5 and 5a.

10 Fig. 5 shows a generator 110 in which a magnet 112 is disposed to be freely movable along the axis of a helical coil 114 shown as a two-layer winding. The coil may be pile wound in any fashion. The axial movement of the magnet 112 and the magnet flux field associated with it generates an electromotive force (e.m.f.) in the coil as the field lines cut the coil to transform  
15 the kinetic mechanical energy of the magnet into electrical energy.

The movement of the magnet is constrained by disposing it within a cylindrical tube 116 around which the coil 114 is wound and the extent of movement is limited by stops. The magnet vibrates axially within the tube in sympathy with the vibration of a mechanical device, such as a power tool to  
20 which the tube 116 is mounted. To enhance the to-and-fro vibration of the magnet 112, at least one of the tube ends is closed by a resilient stop device, such as a spring, against which the magnet bounces or recoils when it strikes the device. Preferably each end of the tube is closed in similar manner as indicated by resilient devices 118a and 118b. The tube is of a "slippery"  
25 plastics to provide low friction for the axial vibration of the magnet. Polytetrafluoroethylene (PTFE) is an example.

The magnet 112 is a bar-type of permanent magnet and preferably of relatively high length (L) to diameter or width ratio to reduce its self-demagnetisation. The coil is of about the same length L as the magnet and the resilient devices 118a and 118b are spaced at a distance D from the  
5 respective nearer end of the coil to allow the magnet to fully emerge from the coil. D is preferably at least 50% of L.

The springs or other resilient devices 118a and 118b not only serve to retain the magnet 112 in the tube 116 but also to cushion the magnet against violent shock. Furthermore, the assembly may be designed to have a  
10 resonance at a frequency of the vibrating source so as to enhance the transfer of vibration of the source into vibrations of the magnet.

The vibration of the magnet 112 within coil 114 generates voltages of both polarities at a given end of the coil with respect to the other. As shown in Fig. 5a the coil 114 may be connected into a full-wave rectifier bridge 120 to  
15 generate a single polarity of voltage/current output used, for example, to charge a smoothing/storage capacitor C.

The physical size of the generator of Fig. 5 is presently contemplated as ranging from a magnet which is a piece of magnetised wire disposed within a tube the size of a drinking straw – certain of the many such straws are of a  
20 sufficiently "slippery" material – to a magnet fitting a tube of 1 cm diameter or more.

The generator embodiment of Fig. 5 utilizes a straight tube. The embodiment could be realised in an arcuate or other curved form. Other forms of reciprocal movement along a predetermined path between  
25 prescribed limits include a magnet constrained to move in an arcuate path about an axis.

As already stated the signal communication from the adaptor 20 to the processing unit could be done by a wire-less method, such as an IR link, rather than through the cable 22. As described the cable 22 allows power to be distributed from the unit 30 to adaptor 22 or vice versa or a combination of the two. To avoid use of the cable altogether requires the adaptor 20 and unit 30 to have separate sources of power in which case the generator of Fig. 5 may be sufficient to fully power adaptor 20.



Claims

1. A torque transducer assembly comprising:
  - a housing having an opening therethrough;
  - 5 a torque transmission shaft extending in said opening and rotatable about an axis extending through said opening, said shaft having respective end portions accessible from exteriorly of said housing,
  - a torque transducer element integral with, or carried by, said shaft to emanate a magnetic field dependent on the torque in the shaft,
  - 10 a magnetic field sensor arrangement located within said housing adjacent said element for sensing the torque-dependent field, said sensor arrangement being operable to provide a torque-dependent signal; and
  - means for communicating said torque-dependent signal to a signal externally of the assembly.
- 15 2. A torque transducer assembly as claimed in Claim 1 in which one end portion of said shaft projects exteriorly of said housing and provides an output portion of the shaft.
3. A torque transducer assembly as claimed in Claim 1 or 2 in which said housing is configured to enable it to be secured against rotation.
- 20 4. A torque transducer assembly as claimed in Claim 3 further comprising a member having a first portion engaged with the housing and second portion engageable with the body of a power torque tool to secure the housing against rotation with respect to said body.

5. A torque transducer assembly as claimed in Claim 4 in which said member comprises a helical spring.
6. A torque transducer assembly as claimed in any one of Claims 1 to 5 in which said magnetic field sensor arrangement comprises at least one  
5 magnetic field sensor device.
7. A torque transducer assembly as claimed in Claim 6 in which said magnetic field sensor arrangement further comprises a circuit into which the magnetic field sensor device(s) is connected, the circuit and magnetic field sensor device(s) being supported by said housing, the circuit being operable  
10 to output signals representing torque through the means for communicating.
8. A torque transducer comprising a torque transducer assembly which is as claimed in any one of Claims 1 to 7 and a signal processing unit in communication with said torque transducer assembly for processing said torque-dependent signals, wherein said signal processing unit is operable to  
15 process pulse signals representing pulses of torque and is responsive to the amplitude of each pulse signal with reference to the quiescent signal level on which it is imposed.
9. A torque transducer as claimed in Claim 7 or 8 wherein the means for communication utilizes a wire-less (free of wire connection) form of  
20 communication.
10. A torque transducer comprising a torque transducer assembly which is as claimed in Claim 8 and a signal processing unit connected to said means for communication by an electrical cable, said signal processing unit comprising a circuit into which the magnetic field sensor device(s) is  
25 connected through the cable, the circuit being operable to output signals representing sensed torque.

11. A transducer as claimed in Claim 10 in which signal processing unit is operable to process pulse signals representing pulses of torque and is responsive to the amplitude of each pulse signal with reference to the quiescent level on which it is imposed.
- 5 12. An electrical power generator comprising a permanent magnet disposed to move freely back-and-forth along a predetermined path between prescribed limits, a coil winding through which the predetermined path extends, the magnet and coil being so arranged that back-and-forth movements of the magnet with respect to the coil generates e.m.f.s in the coil,  
10 and a rectifier arrangement for deriving voltage of a given polarity from the e.m.f.s.
13. An electrical power generator as claimed in Claim 12 in which at least one of said prescribed limits is defined by a resilient stop device from which the permanent magnet impinging thereon rebounds.
- 15 14. An electrical power generator as claimed in Claim 12 or 13 in which said coil is wound about a portion of said predetermined path, said magnet has N-S poles aligned on said path and said prescribed limits are spaced from respective ends of said path portion.
- 20 15. An electrical power generator as claimed in Claim 12 wherein the spacing between the prescribed limits and respective ends of said path portion is not less than half the length of the magnet.
16. An electrical power generator as claimed in Claim 14 or 15 in which said coil has a length along said predetermined path about equal to the length of the magnet.
- 25 17. An electrical power generator as claimed in any one of Claims 12 to 16 in which said predetermined path is straight.

18. An electrical power generator as claimed in any one of Claims 12 to 17 further comprising a tube in which the predetermined path extends, the magnet being disposed within the tube and the coil being wound about a portion of the tube.

5 19. An electrical power generator as claimed in Claim 18 and 13 in which the or each resilient stop device is located within the tube.

20. An electrical power generator as claimed in any one of Claims 12 to 19 in which said rectifier arrangement comprises a full-wave rectifier connected across said coil.

10 21. A pulsed-type power torque tool to which an electrical power generator as claimed in any one of Claims 12 to 20 is mounted whereby the magnet is reciprocated back-and-forth along said predetermined path with respect to the coil by the vibration of the power torque tool when in operation.

22. A torque transducer assembly comprising

15 a housing having an opening therethrough,

a torque transmission shaft disposed in said housing for rotation about an axis extending through said opening, said shaft having a first portion supported in an annular bush secured to the housing and from which first portion and output portion of the shaft projects,

20 said first portion having a torque transducer element integral therewith, or carried thereby, to emanate a magnetic field dependent on the torque in the shaft, a magnetic field sensor arrangement embedded in said bush adjacent said element for providing a torque-dependent signal,

said shaft having a second portion distal said output portion and at  
25 least partially contained within said opening,

said second portion being of larger cross-section than said first portion and abutting said bush,

first means for locating said second portion to rotate with respect to said housing and second means for applying axial force between the housing  
5 and said second portion to maintain same in abutment.

23. A torque transducer assembly as claimed in Claim 22 in which said first means comprises a bushing located in a circumferential groove around said second portion and engaging an inner surface of said opening.

24. A torque transducer as claimed in Claim 23 in which said second  
10 means comprises a retainer ring secured in said opening to apply an axial force to said bushing.




Fig. 1








Fig. 2

Drawing: Cross section of the Goliatth torque sensor.





**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**